

FFE Fedora



Cod	Format	Latime	Lungime	Compozitie	Greutate
FFE	rola	295 cm	± 28 m	100 % poliester	315 g/m ²

Reactie la foc 	IFR - IGNIFUGAT PERMANENT rezistent la foc si nu intretine arderea
---------------------------	--

Certificat de ignifugare 	UNI 9177 class 1, EN 13773 class 1, DIN 4102 class B1 NFP 92 503-507 class M1, BS 5867 part 2 type B & C IMO FTP Code 2010 - Part 7
-------------------------------------	---

Grad de opacitate	● ● ● ● ● -cu captuseala
Grad de absorbtie a luminii	● ● ● ● ● -cu lumina din orice directie
Rezistenta la frecare	● ● ● ● ● - >80.000 c Martindale



Pentru pictura	● ● ● ● ●
Pentru print digital	● ● ● ● ●
Absorbția sunetului - Montaj - Tip G-150 (150 mm fata de peretele reflexiv)	Conform ISO 11654 Coeficient masurat de absorbtie a sunetului: $\alpha_w = 0.60$ (MH) Clasa de absorbtie a sunetului: C
Bariera fonica	● ● ● ● ● Conform ISO 16283 Conform ASTM E413
Disponibilitate	la metru la rola confectionate la cerere
Culori personalizate	Disponibile la cerere Cantitate minima ± 300 ml